WPIR-141 WLAN 802.11g **PCI Adapter**

Turbo mode Up to 75Mbps

Up to Turbo mode 75Mbps

SparkLAN WPIR-141 WLAN 02.11g PCI Adapter support Turbo mode with up to 75Mbps data rat while you connect to Realtek-based WAPR-141 AP and WRTR-141 Router.

The WPIR-141 PCI Adapter connects you with 802.11g networks at! And for added versatility, WPIR-141 is also capable of inter-operating with all the 802.11b wireless products found in homes, businesses, and public wireless hotspots around the country.

SparkLAN WPIR-141 PCI Adapter installs in most desktops so that you can relocate your computers to places you want at home or anywhere in the office without the cost and hassle of running network cables

FEATURES & BENEFITS

- Support Turbo mode up to 75Mbps
- ♦ Operates in the 2.4GHz
- Wireless link speeds up to 54Mpbs; 5 times faster than 802.11b devices.
- ♦ Up to 128-bit WEP, WPA with TKIP, 802,1x, AES
- Support Windows XP/2000/ME/98SE

SPECIFICATIONS

CONNECTIONS

MADE

ERSY

HARDWARE	
Chipset	Realtek RTL8225
Interface	PCI Rev2.2 Compliant
LED Indicators	Link
Antenna	Reverse SMA connector with 2dBi detachable antenna
RADIO CHARACTERISTICS	
Standards	IEEE 802.11g, 802.11b
Frequency Bands	2.4GHz
Modulation Tech	802.11b: CCK,DQPSK, DBPSK 802.11g: OFDM
Media Access Protocol	CSMA/CA with ACK
Transmit Power	802.11g :16 dBm 802.11b :18 dBm
Receive Sensitivity	11 Mbps 10-5 BER @ -86 dBm, TYP 54 Mbps 10-5 BER @ -68 dBm, TYP
Data Rates	802.11b: 11Mbps, 5.5Mbps, 2Mbps, 1Mbps, auto fallback 802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps
Operating Range	Open space : 100-300m ; Indoor: 30-100m
- p g g -	* The performance various depend on environment.
ENVIRONMENTAL SPECIFIC	
ENVIRONMENTAL SPECIFIC	ATIONS
ENVIRONMENTAL SPECIFIC	ATIONS 152x 122 x 22 mm (LxWxH)
ENVIRONMENTAL SPECIFIC Dimension Weight	ATIONS 152x 122 x 22 mm (LxWxH) 50g
ENVIRONMENTAL SPECIFIC Dimension Weight Temperature	ATIONS 152x 122 x 22 mm (LxWxH) 50g 0°C to 40°C(Operating),-40°C to 85°C(Storing)
ENVIRONMENTAL SPECIFIC Dimension Weight Temperature Humidity	ATIONS 152x 122 x 22 mm (LxWxH) 50g 0°C to 40°C(Operating),-40°C to 85°C(Storing) 10~90% Non-condensing
ENVIRONMENTAL SPECIFIC Dimension Weight Temperature Humidity Power Consumption	ATIONS 152x 122 x 22 mm (LxWxH) 50g 0°C to 40°C(Operating),-40°C to 85°C(Storing) 10~90% Non-condensing
ENVIRONMENTAL SPECIFIC Dimension Weight Temperature Humidity Power Consumption SOFTWARE FEATURES	ATIONS 152x 122 x 22 mm (LxWxH) 50g 0°C to 40°C(Operating),-40°C to 85°C(Storing) 10~90% Non-condensing 3.3V±5%
ENVIRONMENTAL SPECIFIC Dimension Weight Temperature Humidity Power Consumption SOFTWARE FEATURES Operating Systems	ATIONS 152x 122 x 22 mm (LxWxH) 50g 0°C to 40°C(Operating),-40°C to 85°C(Storing) 10~90% Non-condensing 3.3V±5% Windows XP/ME/2000/98SE
ENVIRONMENTAL SPECIFIC Dimension Weight Temperature Humidity Power Consumption SOFTWARE FEATURES Operating Systems Security	ATIONS 152x 122 x 22 mm (LxWxH) 50g 0°C to 40°C(Operating),-40°C to 85°C(Storing) 10~90% Non-condensing 3.3V±5% Windows XP/ME/2000/98SE 64/128-Bit WEP, WPA, TKIP, 802.11X, AES
ENVIRONMENTAL SPECIFIC Dimension Weight Temperature Humidity Power Consumption SOFTWARE FEATURES Operating Systems Security Management	ATIONS 152x 122 x 22 mm (LxWxH) 50g 0°C to 40°C(Operating),-40°C to 85°C(Storing) 10~90% Non-condensing 3.3V±5% Windows XP/ME/2000/98SE 64/128-Bit WEP, WPA, TKIP, 802.11X, AES
ENVIRONMENTAL SPECIFIC Dimension Weight Temperature Humidity Power Consumption SOFTWARE FEATURES Operating Systems Security Management CERTIFICATION	ATIONS 152x 122 x 22 mm (LxWxH) 50g 0°C to 40°C(Operating),-40°C to 85°C(Storing) 10~90% Non-condensing 3.3V±5% Windows XP/ME/2000/98SE 64/128-Bit WEP, WPA, TKIP, 802.11X, AES
ENVIRONMENTAL SPECIFIC Dimension Weight Temperature Humidity Power Consumption SOFTWARE FEATURES Operating Systems Security Management CERTIFICATION FCC , CE	ATIONS 152x 122 x 22 mm (LxWxH) 50g 0°C to 40°C(Operating),-40°C to 85°C(Storing) 10–90% Non-condensing 3.3V±5% Windows XP/ME/2000/98SE 64/128-Bit WEP, WPA, TKIP, 802.11X, AES Web-based management

One Quick Installation Guide






WAPR-141 AP

WRTR-141 AP Router

SparkLAN Communications Inc., All Rights Reserved. SparkLAN may make changes to specifications and descriptions at any time without prior notice.



TEL:886-2-26591880

service@sparklan.com